



Riga Wood
Latvijas Finieris Group



Riga Lacquer

Riga Lacquer is a birch throughout plywood with a lacquered surface finish on one or both faces.

Applications

Riga Lacquer is a high quality decorative panel for interior applications, with a naturally beautiful wooden structure and improved surface properties suitable for civil projects as well as industrial end uses.



LIGHT BUILDING

Decorative wall & Ceiling linings
Joinery, furniture & Shopfittings



PACKAGING

Die boards



ROAD TRANSPORT

Buses
Passenger cars

Major advantages

Durable decorative surface with gloss or matte finishing Naturally beautiful wood appearance Wide range of different coloured lacquers Flame reaction decreasing lacquering system available

Ready to use surface panel representing substantial time and cost saving Surface is resistant to commonly used chemicals and surface impact, easy to clean Sustainable product with long life span

Further processing

Riga Lacquer can be further processed according to customer's specification with: cut-to-size, CNC, drilling, milling, jointing, edge machining, and assembling in sets.

For applications where insulation and acoustic performance are required, perforated and grooved acoustic panels are possible. More information available in the Acoustic panel leaflet.

Coating and surface properties

Different lacquering systems are available on request:

- LC: acid catalysed solvent based
- LPU: acrylic-based polyurethane
- LUV: UV curing
- FRC: water-based flame retardant

Standard semi-gloss finishing with 25 gloss units, from 5 to 45 gloss units available on request (at G60° according to ISO 2813).

Colour: by default transparent colour. Pigmented/coloured lacquering systems available on request.

Edge sealing

The edges can be sealed upon request.

Panel sizes

1220 / 1250 mm x 2440 / 2500 / 2745 / 2750 / 3000 / 3050 mm
1500 / 1525 mm x 2440 / 2500 / 2745 / 2750 / 3000 / 3050* mm
2440 / 2500 mm x 1220 / 1250 mm

* Available for Riga Lacquer LUV

Standard thicknesses

6,5, 9, 12, 15, 18, 21, 24 mm
Other thicknesses available on request.

Gluing classes

Riga Wood birch plywood is glued with weather and boil-proof phenol formaldehyde or lignin phenol formaldehyde resin adhesive according to EN 314/Class 3 Exterior.

Bonding with moisture resistant low emission melamine-urea-formaldehyde resin according to EN 314 / Class 1 and BS 1203 / H1 possible.

Formaldehyde emission

Riga Lacquer birch plywood formaldehyde emission level is significantly below EN 13986 Class E1.

Base plywood

Riga Lacquer with optically good peeled veneer in S (II) and BB (III) grade (according to the requirements of EN 635) and as well as on Riga Decor with slice veneer surfaces in birch, oak, ash, beech, and others.

Riga Lacquer

Tolerance

Nominal thickness, mm	6.5	9	12	15	18	21	24
Number of plies	5	7	9	11	13	15	17
Lower limit, mm	6.1	8.8	11.5	14.3	17.1	20	22.9
Upper limit, mm	6.9	9.5	12.5	15.3	18.1	20.9	23.7

Moisture content affects plywood dimensions; indicated sizes and thicknesses relate to a moisture content $9 \pm 3\%$.

Parameter	Tolerance
Length, width (mm) < 1000	± 1 mm
Length, width (mm) – 1000..2000	± 2 mm
Length, width (mm) > 2000	± 3 mm
Squareness tolerance	± 1 mm/m
Edge straightness	± 1 mm/m

Size, squareness and thickness tolerances fulfil the requirements of EN 315.

Customised tolerances available on request.

Sustainability

We strongly believe that wood-based products in industrial use are a great option for carbon storage and a big part of the solution to achieve climate change mitigation. The key principles of sustainability and responsible governance are deeply rooted in our company's traditions and we aim to further develop our initiatives by actively engaging with stakeholders, material suppliers and clients.

Storage

Plywood must be stored in a well ventilated, weather protected area with the panels stacked both horizontally and level.

Additional information is available in the Riga Wood plywood handbook:
<https://www.finieris.com/en/downloads/brochures>

The provided information is for reference only and Riga Wood reserves the right to amend and supplement the specifications of manufactured products without prior notice. Wood is a living material; therefore, each panel is unique and minor differences are possible. Riga Wood does not guarantee a product's compliance with the requirements of any specific purpose.